

600W DAB

600 W DAB TRANSMITTER



DAB TRANSMITTER



HIGH EFFICIENCY



MULTI-PLATFORM



MULTI INPUT



MULTI-STANDARD
DVB-T/T2 ATSC/ATSC 3.0
ISDB-Tb DTMB NTSC (analog)



WIDE BAND



AIR COOLED



GNSS
(GPS, GLONASS, BEIDU, GALILEO)



MONITORING
SNMP, WEB BASED GUI,
DRY CONTACTS



The PCM 600 DAB is the air cooled DAB Transmitter from PCM line.

600 Wrms DAB.

Low Consumption, Compact and Easy to maintain, with a clear and intuitive design, it is Syes next generation of air cooled transmitters.

The PCM family is designed to be the most efficient, robust and high performance transmitters of the digital era.

- ☐ Multimode platform: Transmitter, Heterodyne Transposer, Regenerative Transmitter, Gap Filler and Single Frequency Echo Canceller
- ☐ Multi Input: ETI Hitless Switch (Priority customer settable) + 2 EDI Ethernet A/V for analog broadcasting + 1xSFP (optical/electrical), Nr.1 SAT (DVB-S2/SX with CAMSlot) Double Transmitter: Includes the ability to transmit two DAB+ frequencies with the same transmitter
- ☐ COT Feature (Continuity of Transmission): null packet insertion to compensate for micro input interruptions
- ☐ The most advanced manual, automatic and adaptive linear and nonlinear pre-corrector.
- ☐ Sky-High efficiency to minimize energy consumption and OPEX up to 34%;
- ☐ Fully frequency agile without need for any tuning or trimming.
- ☐ ON Board GNSS receiver (GPS, GLONASS, BEIDU, GALILEO) for SFN Applications.
- ☐ USB input to fast save/load configurations.
- ☐ Use of tools reduced almost to zero including pallet replacement.
- ☐ Dual Independent temperature controlled low-noise fans
- ☐ Remote control via SNMP, friendly web browser GUI, no need of plug-in or apps, dry contacts.

DAB

AIR COOLED

sales@syes.eu | www.syes.eu

600W DAB

600 W DAB TRANSMITTER

DAB

AIR COOLED

TECHNICAL SPECIFICATIONS

RF OUTPUT

Output power*	• 600 Wrms DAB
Spurious / Harmonics	EN 302-296-2 / EN 302 077
Shoulders/MER	Typical: >50dB / >35db
Connector / Impedance	7/16" (f) - 50 Ohm
Bandwidth	DAB
Frequency stability	1 Hz
Final Stage	N° 4 final pallets.
Amplification Class:	HE class

GENERAL

Mechanical

Composition	Stand alone transmitter 3 S.U.
Dimensions (WxHxD mm - Weight)	483 mm / 132 mm / 500 18 kg

Cooling

Cooling System	Air Cooled
Cooling redundancy	Dual fan

Environmental

Relative humidity	95% max. (non-condensing)
Operation temperature range	0° to 50°C
Storage temperature range	-20° to 70°C
Max. installation altitude	4.800 m a.s.l. (higher altitudes kit on request)

Power supply & Safety

Voltage***	90-264 Wide Range @ 47 to 63 Hz (auto range p.s.) power factor > 0.98
Safety /EMC	EN 60215 (IEC 21S), EN301-489-53, FCC-73, IS09001-2010. RED 2014/53/UE, RoHS 2002/93/EC
Safe Operations	Interlock Circuit provided and configurable.

DTV MODULATIONS

<u>DAB</u>	
Standard	DAB, DAB+ (Ref. Standards EN 3000401, EN 302077-2, EN 300799) DMB, TS 102428
Inputs	2xASI hitless switching (SFN), 2xGBE (EDI ProMPEG COP3) - Electrical + 1xSFP GBE (Opt./Elec)
DAB modes	I, II, III, IV
RF channel Bandwidth	1.536 MHZ blocks

*: Power outputs are subject to change due to out-of-band regulations and the required shoulder attenuation / MER, voltage, channel of operation and type of RF output filter. VSWR: 2:1

** : HE High Efficiency Syes transmitting platform are WIDE BAND native, without any need for software or hardware change, tuning or other setting. Efficiency depends on several parameters such as operating standard and frequency, output power settings, spectrum performances, environmental conditions etc.

***: Single mains supply per cabinet, with power isolator switch, accessible from the outside

SY
es

SY.E.S. S.r.l. • Via Zanella, 21

20851 Lissone (MB) Italy Tel. +39.039.9897.1

Fax +39.039.9897.363 C.F. / P.IVA 06358330964

sales@sy.es.eu | www.syes.eu

600W DAB

600 W DAB TRANSMITTER

DAB

AIR COOLED

DIGITAL ADAPTIVE PRECORRECTION	
Type	Linear / non linear; selectable
Clipping	12 dB
Operation mode	Continuous / Automatic (triggering: time/shoulder level)
Precorrection status	Running/Stopped
PAPR	Provided
REPEATER	
Type	SFN gap filler, transposer and MFN re transmitter
RF input	N-Connector
Rfm frequency range	146 to 861 MHz
Input level	-10dBm to -60dBm (SFN Gap filler) -20dBm to -70dBm (QEF reception)
Input ret. Loss	better than -16 dB
RF in connector	N type . 50 Ohm
Echo cancellation	Resilient to static and dynamic echoes
Residual echo suppression	up to more than 30 dB (30dB are obtained at 0dB input echo)
Noise figure	max 10 dB (SFN Gap filler) max 8 dB (Transposer)
Immunity to other channel	
N+1	OFDM/OFDM > 30 dB
others	OFDM/OFDM > 40 dB
SATELLITE TRANSPOSER	
SatTV standard	DVB-S - DVB-S2 - EN300421
Frequency range	950 - 2150 MHz (Ku band)
Signal level	-65 to -25 dBm
Connector	SMA f - CAM slot (Cond. Access)
LNB control	Available through RF input. PS, polarity / band selection: by standard 13/18VDC and 22kHz signaling
CLOCK AND SYNCHRONIZATION	
Internal clock	OCXO single oven or dual oven (optional)
External 10 MHz 1pps reference	BNC (F). Impedance: 50 ohm / high (selectable). Level: -5 to +10 dBm
NTP Server	Available
SFN	SFN resolution 1100 ns SFN configurable delay ± 500 ms
Stability	time: max $\pm 10^{-7}$ /year - temperature: max $\pm 2.5 \cdot 10^{-8}$ (-20°C to +70 °C)
MONITORING	
Local Full Monitoring and Control	Local operation through LCD display and keyboard located on the front panel
Front RJ-45 Rear RJ-45	Local operation through a Web Server Graphical User Interface, Remote Network management (via SNMP)
FW & SW Upgrade	Via web pages, self-upgrade function available via OTA or remote server.
GUI	Web Server Graphical User interface xHTML based
SNMP	V2c / V3 provided

SV
Yes