

2,5 kW COFDM - 3 kW ATSC - 5,2 kWps (Analog) - 3 kW DAB 2,5 kW VHF-BIII TV TRANSMITTER LQ



TV TRANSMITTER



HIGH EFFICIENCY



HOT PLUG-IN POWER
SUPPLY/PSU



MULTI-PLATFORM



MULTI INPUT



MULTI-STANDARD
DVB-T/T2 ATSC/ATSC 3.0
ISDB-Tb DTMB NTSC (analog)



MONITORING
SNMP, WEB BASED GUI,
DRY CONTACTS



WIDE BAND



HOT SWAPPABLE
AMPLIFIER



LIQUID COOLED



GNSS
(GPS, GLONASS, BEIDU, GALILEO)



FRONT VIEW



- ☐ Multistandard: ATSC (including ATSC3.0), ISDB-T, DTMB, DVB-T/T2, Analog, DAB.
- ☐ High energy efficiency to minimize consumption and OPEX .
- ☐ Automatic digital static or adaptive Linear and Non-Linear Pre-correction.
- ☐ Hot Pluggable Power Amplifiers.
- ☐ Power Amplifiers with triple redundant Hot Plug-in power supplies.
- ☐ Temperature-controlled closed liquid cooled system for better efficiency and performance equipped with Dual Redundant Pump plug-In (tool-free pump swap) and dual-blower heat exchanger.
- ☐ Multi input: 2x ASI seamless switch, 2x SAT (S2 with CAMSlot), 2x IP Ethernet, 2x ETI/EDI + 1xSFP (optical/electrical), A/V for analog broadcasting.
- ☐ USB input to fast save/load configurations.
- ☐ Built-in GNSS receiver (GPS, GLONASS, BEIDU, GALILEO) for SFN application.
- ☐ Remote control via SNMP, friendly web browser GUI, no need of plug-in or apps, dry contacts.

The P75 Line is the multi amplifier liquid cooled Transmitter family from SYES.

P75-02 is equipped with Driver (Dual Driver Option) and N°2 plug-In Amplifiers.

It is equipped with High Efficiency Wideband UHF/VHF and Low VHF state-of-the-art amplifiers characterized by high-power density and excellent signal quality granting optimal parameters such as shoulder attenuation and MER.

The P75 amplifiers are hot pluggable and are equipped with 3x redundant Hot Plug-in power supplies each, assuring the maximum reliability and the easiest maintenance.

TV

LIQUID COOLED

2,5 kW COFDM - 3 kW ATSC - 5,2 kWps (Analog) - 3 kW DAB 2,5 kW VHF-BIII TV TRANSMITTER LQ

TV
LIQUID COOLED

TECHNICAL SPECIFICATIONS	
RF OUTPUT	
Output power*	2500 Wrms COFDM 3000 Wrms ATSC 5200 Wp.s. ANALOG 3000 Wrms DAB
Spurious / Harmonics	EN 302-296-2
Shoulders/MER	Typical: >48dB/>38dB
Connector/ Impedence	1 5/8", other available
Bandwidth	VHF Band BIII (170MHz-230MHz)
Frequency stability	1 Hz
Amplification Class:	Either High efficiency (Doherty type) or AB class available
Final Stage:	No. 2 Amplifiers each with No. 6 Pallets with 4 final transistors each (LDMOS latest technology).
GENERAL	
Mechanical	
Composition (Main components in one rack 44U)	1x Exciter 2x P75-V Amplifier 1x Tx control logic 1x cooling drawer, close vase type, dual pump.
Dimensions (WxHxD mm - Weight)	600x2320x1100 340 kg
Cooling	
Cooling System	Liquid cooling, close vase type
Cooling redundancy	Single or dual pump / single or dual heat exchanger
Environmental	
Relative humidity	95% max. (non-condensing)
Operation temperature range	0° to 50°C
Storage temperature range	-20° to 70°C
Max. installation altitude	4.600 m a.s.l. (higher altitudes kit on request)
Power supply & Safety	
Voltage	208/ 400 Vac (three phase) 47 to 63 Hz (auto range p.s.) power factor > 0.98
Power Supply	3x Power supplies In hot plug-in configuration each amplifier. 2+1 PS redundancy configuration available
Efficiency** (typical value referred to OFDM modulation)	Up to 50%
Safety /EMC	EN 60215 (IEC 215), EN301-489-53, FCC-73, IS09001-2010. RED 2014/53/UE, RoHS 2002/93/EC

*: Power outputs are subject to change due to out-of-band regulations and the required shoulder attenuation / MER, voltage, channel of operation and type of RF output filter.

** : Efficiency depends on several parameters such as operating standard and frequency, output power settings, spectrum performances, environmental conditions etc.

SYES

SY.E.S. S.r.l. • Via Zanella, 21
20851 Lissone (MB) Italy Tel. +39.039.9897.1
Fax +39.039.9897.363 C.F. / P.IVA 06358330964
sales@syes.eu | www.syes.eu

2,5 kW COFDM - 3 kW ATSC - 5,2 kWps (Analog) - 3 kW DAB 2,5 kW VHF-BIII TV TRANSMITTER LQ



TV TRANSMITTER

DTV MODULATIONS													
ATSC 3.0													
Standard				ATSC 3.0: TG3/S32 Physical Layer. STL									
Inputs ****				2xASI BNC (H) , ohm / 2x TS0iP 10/100/1000 RJ45.									
Guard interval				192, 384, 512, 768, 1024, 1536, 2048, 2432,3072, 3648, 4096 and 4864									
Code Rate/ Constellation	2 / 15	3 / 15	4 / 15	5 / 15	6 / 15	7 / 15	8 / 15	9 / 15	10 / 15	11 / 15	12 / 15	13 / 15	
QPSK	✓	✓	✓	✓	✓	✓	✓	✓		✓			
16QAM			✓	✓		✓	✓	✓		✓			
64QAM		✓	✓	✓	✓	✓	✓	✓	✓	✓			
256QAM			✓	✓		✓	✓	✓	✓	✓			
1024QAM				✓		✓	✓	✓	✓	✓	✓		✓
4096QAM						✓		✓		✓	✓	✓	✓
DVB-T/H-T2													
Standard				EN300744. EN302304. EN302755. TS 102831. TS 102 773 (T2-MI)									
Inputs ****				2*ASI BNC, 75 ohm / 3xTS0iP 10/100/1000 RJ45.									
FFT Size				1K (DVB-T2), 2K, 4K, 8K, 16K (DVB-T2), 32K (DVB-T2) incl. ext. carrier modes									
Code rate				1/2. 2/3. 3/4. 5/6. 3/5 (DVB-T2). 4/5 (DVB-T2) plus 1/3, 2/5 for T2 Lite									
Guard interval				1/32,1/16. 1/8.1/4. 19/256 (DVB-T2), 19/128 (DVB-T2), 1/128 (DVB-T2)									
Constellation				QPSK. 16QAM. 64QAM. 256QAM (DVB-T2). Rotated and no rotated (DVB-T2)									
ISDB-Tb													
Standard				ARIB STB-B31, TR-B14									
Inputs ****				2xASI BNC, 75 ohm / 3xTS0iP 10/100/1000 RJ45									
FFT Size				2K, 4K, 8K									
Code rate				1/2, 2/3, 3/4, 5/6, 7/8									
Guard interval				1/4, 1/8, 1/16, 1/32									
Hierarchical Transmission				Up to 3 layers									
Constellation				QPSK, 16QAM, 64QAM									
ATSC													
Standard				ATSC A/53. A/54. A/64. A/153. A/110B. SMPTE-310M									
Inputs ****				2xASI BNC (F)>. 75 ohm /2xTS0iP 10/100/1000 RJ45.									
Constellation				8VSB									
Symbol rate				0.76 Msmblos/s									
Data rate				19.39 Mbits/s									
Trellis coding				2/3									
Reed-Solomon encoder				207 / 187 / 10									
DTMB													
Standard				DTMB (GB20200/2006)									
Inputs ****				2xASI BNC (H), 75 ohm /2xTS0iP 10/100/1000 RJ45									
FFT Size				Single carrier/ 3780									
Constellation				64 QAM, 32 QAM, 16QAM, 4QAM, 4QAM NR									
Code rate				0,4-0,6-0,8									
Data rate				24,365 Mb/s									
Frame header				420 Symbols/595 Symbols/ 945 Symbols									
DIGITAL ADAPTIVE PRECORRECTION													
Type				Linear / non linear; selectable									
Clipping				12 dB									
Operation mode				Continuous / Automatic (triggering: time/shoulder level)									
Precorrection status				Running/Stopped									
PAPR				Provided									

**** Type and number of inputs depends on Exciter HW configuration

TV
AIR COOLED

sales@syes.eu | www.syes.eu

2,5 kW COFDM - 3 kW ATSC - 5,2 kWps (Analog) - 3 kW DAB 2,5 kW VHF-BIII TV TRANSMITTER LQ

TV
LIQUID COOLED

ANALOGUE MODULATIONS	
Standard	PAL std. B/G, H, K, 1, 11, M, N - NTSC Std. M - SECAM D/K
Ref. Standard	ITU-R BT.470-6
Audio	Mono IRT
Modulation /amplification	Common
Video input	1V pp (0.5 to 2 V) (OC component level in the range -5 to 5 V) - Ret. loss better than -30 dB (0 to 6 MHz) (75 W)
Audio input	6 dBm $\pm$ 6 dB (Df= 25 to 50 kHz) - Ret. loss: better than -30 dB (40 Hz to 15 kHz) (600 W, bai.)
Video Connector	1xBNC female. 75 Ohm
Audio Connector	DB9 with patch cable for 2xXLR female, 600 W (IRT config.: 2 inputs)
REPEATER	
Type	SFN gap filler, transposer and MFN re-transmitter
RF input	
Rfm frequency range	146 to 861 MHz
Input level	-10dBm to -60dBm (SFN Gap filler) -20dBm to -70dBm (QEF reception)
Input ret. Loss	better than -16 dB
RF in connector	N type . 50 Ohm
Echo cancellation	
Residual echo suppression	up to more than 30 dB (30dB are obtained at 0dB input echo)
Noise figure	max 10 dB (SFN Gap filler) max 8 dB (Transposer)
Immunity to other channel	
N+1	OFDM/OFDM > 30 dB
others	OFDM/OFDM > 40 dB
SATELLITE TRANSPOSER	
SatTV standard	DVB-S - DVB-S2 - EN300421
Frequency range	950 - 2150 MHz (Ku band)
Signal level	-65 to -25 dBm
Connector	SMA f - CAM slot (Cond. Access)
LNB control	Available through RF input. PS, polarity / band selection: by standard 13/18VDC and 22kHz signaling
CLOCK AND SYNCHRONIZATION	
Internal clock	OCXO single oven or dual oven (optional)
External 10 MHz reference	BNC (F). Impedance: 50 ohm / high (selectable). Level: -5 to +10 dBm
External 1pps reference	BNC (F). Impedance: 50 ohm / high (selectable)
SFN	SFN resolution 1100 ns SFN configurable delay $\pm$ 500 ms
Stability	time: max $\pm$ 10-7 /year - temperature: max $\pm$ 2.5 10-8 (-20°C to +70 °C)
MONITORING	
LCD Display	Local operation through LCD display and keyboard located on the front panel
Front RJ-45 Rear RJ-45	Local operation through a Web Server Graphical User Interface, Remote Network management (via SNMP)
GUI	Web Server Graphical User Interface xHTML based
SNMP	V2c / V3 provided

SYES

SY.E.S. S.r.l. • Via Zanella, 21
20851 Lissone (MB) Italy Tel. +39.039.9897.1
Fax +39.039.9897.363 C.F. / P.IVA 06358330964
sales@syes.eu | www.syes.eu