

2,25 kW COFDM - 3kW ATSC - 7,5 kWps (Analog)

2,25 kW VHF-BI TV TRANSMITTER LQ



TV TRANSMITTER



HIGH EFFICIENCY



HOT PLUG-IN POWER
SUPPLY/PSU



MULTI-PLATFORM



MULTI INPUT



MULTI-STANDARD
DVB-T/T2 ATSC/ATSC 3.0
ISDB-Tb DTMB NTSC (analog)



MONITORING
SNMP, WEB BASED GUI,
DRY CONTACTS



WIDE BAND



HOT SWAPPABLE
AMPLIFIER



LIQUID COOLED



GNSS
(GPS, GLONASS, BEIDU, GALILEO)



FRONT VIEW



- ☐ Multistandard: ATSC (including ATSC3.0), ISDB-T, DTMB, DVB-T/T2, Analog.
- ☐ Fully frequency agile without need for any tuning or trimming.
- ☐ Automatic digital static or adaptive Linear and Non-Linear Pre-correction.
- ☐ Hot Pluggable Power Amplifiers.
- ☐ Power Amplifiers with triple redundant Hot Plug-in power supplies.
- ☐ Temperature-controlled closed liquid cooled system for better efficiency and performance equipped with Dual Redundant Pump plug-In (tool-free pump swap) and dual-blower heat exchanger.
- ☐ Multi input: 2x ASI seamless switch, 2x SAT (S2 with CAMSlot), 2x Ethernet seamless switch.
- ☐ USB input to fast save/load configurations.
- ☐ Built-in GNSS receiver (GPS, GLONASS, BEIDU, GALILEO) for SFN applications.
- ☐ Remote control via SNMP, friendly web browser GUI, no need of plug-in or apps, dry contacts.

The P75 Line is the multi amplifier liquid cooled Transmitter family from SYES.

P75-03/BI is equipped with Driver (Dual Driver Option) and N°3 plug-In Amplifiers.

It is equipped with High Efficiency Wideband UHF/VHF and Low VHF state-of-the-art amplifiers characterized by high-power density and excellent signal quality granting optimal parameters such as shoulder attenuation and MER.

The P75 amplifiers are hot pluggable and are equipped with 3x redundant Hot Plug-in power supplies each, assuring the maximum reliability and the easiest maintenance.

TV
LIQUID COOLED

sales@syes.eu | www.syes.eu

2,25 kW COFDM - 3kW ATSC - 7,5 kWps (Analog)

2,25 kW VHF-BI TV TRANSMITTER LQ

TV
LIQUID COOLED

TECHNICAL SPECIFICATIONS	
RF OUTPUT	
Output power*	• 2250 Wrms COFDM • 3750 Wrms ATSC • 7500 Wp.s. ANALOG
Spurious / Harmonics	EN 302-296-2
Shoulders/MER	Typical: >48dB/>38dB
Connector /Impedence	1 5/8", other available
Bandwidth	Low VHF 47MHz-90MHz
Frequency stability	1 Hz
Amplification Class:	Either High efficiency (Doherty type) or AB class available
Final Stage:	N° 3 Amplifiers with N° 4 Dual transistors Pallets,(LDMOS latest technology).
GENERAL	
Mechanical	
Composition (Main components in one rack 44U)	• 1x Exciter • 3x P75 Amplifier • 1x Tx control logic • 1x cooling drawer, close vase type, dual pump.
Dimensions (WxHxD mm - Weight)	600x2320x1100 310 kg
Cooling	
Cooling System	Liquid cooling, close vase type
Cooling redundancy	Single or dual pump / single or dual heat exchanger
Environmental	
Relative humidity	95% max. (non-condensing)
Operation temperature range	0° to 50°C
Storage temperature range	-20° to 70°C
Max. installation altitude	4.600 m a.s.l. (higher altitudes kit on request)
Power supply & Safety	
Voltage	208/ 400 Vac (three phase) 47 to 63 Hz (auto range p.s.) power factor > 0.98
Power Supply	3x Power supplies In hot plug-in configuration each amplifier. 2+1 PS redundancy configuration available
Safety /EMC	EN 60215 (IEC 215), EN301-489-53, FCC-73, IS09001-2010. RED 2014/53/UE, RoHS 2002/93/EC

*: Power outputs are subject to change due to out-of-band regulations and the required shoulder attenuation / MER, voltage, channel of operation and type of RF output filter.

**: HE High Efficiency Syes transmitting platform are WIDE BAND native, without any need for software or hardware change, tuning or other setting. Efficiency depends on several parameters such as operating standard and frequency, output power settings, spectrum performances, environmental conditions etc.

SYES

SYES.S.r.l. • Via Zanella, 21
20851 Lissone (MB) Italy Tel. +39.039.9897.1
Fax +39.039.9897.363 C.F. / P.IVA 06358330964
sales@syes.eu | www.syes.eu

2,25 kW COFDM - 3kW ATSC - 7,5 kWps (Analog)

2,25 kW VHF-BI TV TRANSMITTER LQ



TV TRANSMITTER

DTV MODULATIONS	
<u>ATSC 3.0</u>	
Standard	ATSC 3.0: A/322:2017, A/324:2018 (STL)
Inputs ****	2xTSolP 10/100/1000 RJ45.
FFT Size	2K, 4K, 8K.
Code rate	1/2, 2/3, 3/4, 5/6,
Guard interval	1/32, 1/16, 1/8, 1/4.
Constellation	QPSK, 16QAM, 64QAM, 256QAM
<u>DVB-T/-H-T2</u>	
Standard	EN300744, EN302304, EN302755, TS 102831, TS 102 773 (T2-MI)
Inputs ****	2x ASI BNC, 75 ohm / 3xTSolP 10/100/1000 RJ45.
FFT Size	1K (DVB-T2), 2K, 4K, 8K, 16K (DVB-T2), 32K (DVB-T2)
Code rate	1/2, 2/3, 3/4, 5/6, 3/5 (DVB-T2), 4/5 (DVB-T2)
Guard interval	1/32, 1/16, 1/8, 1/4, 19/256 (DVB-T2), 19/128 (DVB-T2), 1/128 (DVB-T2)
Constellation	QPSK, 16QAM, 64QAM, 256QAM (DVB-T2). Rotated and no rotated (DVB-T2)
<u>ISDB-Tb</u>	
Standard	ARIB STB-B31, TR-B14
Inputs ****	2xASI BNC, 75 ohm / 3xTSolP 10/100/1000 RJ45
FFT Size	2K, 4K, 8K
Code rate	1/2, 2/3, 3/4, 5/6, 7/8
Guard interval	1/4, 1/8, 1/16, 1/32
Hierarchical Transmission	Up to 3 layers
Constellation	QPSK, 16QAM, 64QAM
<u>ATSC</u>	
Standard	ATSC A/53, A/54, A/64, A/153, A/110B, SMPTE-310M
Inputs ****	2xASI BNC (F) > 75 ohm / 2xTSolP 10/100/1000 RJ45.
Constellation	8VSB
Symbol rate	0.76 Msmblos/s
Data rate	19.39 Mbits/s
Trellis coding	2/3
Reed-Solomon encoder	207 / 187 / 10
DTMB	DTMB
Standard	DTMB (GB20200/2006)
Inputs ****	2xASI BNC (H), 75 ohm / 2xTSolP 10/100/1000 RJ45
FFT Size	Single carrier / 3780
Constellation	64 QAM, 32 QAM, 16QAM, 4QAM, 4QAM NR
Code rate	0,4-0,6-0,8
Data rate	24,365 Mb/s
Frame header	420 Symbols/595 Symbols/ 945 Symbols
**** Type and number of inputs depends on Exciter HW configuration	
DIGITAL ADAPTIVE PRECORRECTION	
Type	Linear / non linear; selectable
Clipping	12 dB
Operation mode	Continuous / Automatic (tnggering: time/shoulder level)
Precorrection status	Running/Stopped
PAPR	Provided

TV
LIQUID COOLED

2,25 kW COFDM - 3kW ATSC - 7,5 kWps (Analog)

2,25 kW VHF-BI TV TRANSMITTER LQ

TV
LIQUID COOLED

ANALOGUE MODULATIONS	
Standard	PAL std. B/G, H, K, 1, 11, M, N - NTSC Std. M - SECAM D/K
Ref. Standard	ITU-R BT.470-6
Audio	Mono IRT
Modulation /amplification	Common
Video input	1V pp (0.5 to 2 V) (OC component level in the range -5 to 5 V) - Ret. loss better than -30 dB (0 to 6 MHz) (75 W)
Audio input	6 dBm $\pm$ 6 dB (Df= 25 to 50 kHz) - Ret. loss: better than -30 dB (40 Hz to 15 kHz) (600 W, bai.)
Video Connector	1xBNC female. 75 Ohm
Audio Connector	DB9 with patch cable for 2xXLR female, 600 W (IRT config.: 2 inputs)
REPEATER	
Type	SFN gap filler, transposer and MFN re-transmitter
RF input	
Rfm frequency range	146 to 861 MHz
Input level	-10dBm to -60dBm (SFN Gap filler) -20dBm to -70dBm (QEF reception)
Input ret. Loss	better than -16 dB
RF in connector	N type . 50 Ohm
Echo cancellation	
Residual echo suppression	up to more than 30 dB (30dB are obtained at 0dB input echo)
Noise figure	max 10 dB (SFN Gap filler) max 8 dB (Transposer)
Immunity to other channel	
N+1	OFDM/OFDM > 30 dB
others	OFDM/OFDM > 40 dB
SATELLITE TRANSPOSER	
SatTV standard	DVB-S - DVB-S2 - EN300421
Frequency range	950 - 2150 MHz (Ku band)
Signal level	-65 to -25 dBm
Connector	SMA f - CAM slot (Cond. Access)
LNB control	Available through RF input. PS, polarity / band selection: by standard 13/18VDC and 22kHz signaling
CLOCK AND SYNCHRONIZATION	
Internal clock	OCXO single oven or dual oven (optional)
External 10 MHz reference	BNC (F). Impedance: 50 ohm / high (selectable). Level: -5 to +10 dBm
External 1pps reference	BNC (F). Impedance: 50 ohm / high (selectable)
SFN	SFN resolution 1100 ns SFN configurable delay $\pm$ 500 ms
Stability	time: max $\pm$ 10-7 /year - temperature: max $\pm$ 2.5 10-8 (-20°C to +70 °C)
MONITORING	
LCD Display	Local operation through LCD display and keyboard located on the front panel
Front RJ-45	Local operation through a Web Server Graphical User Interface, Remote
Rear RJ-45	Network management (via SNMP)
GUI	Web Server Graphical User Interface xHTML based
SNMP	V2c / V3 provided

SYES

SY.E.S. S.r.l. • Via Zanella, 21
20851 Lissone (MB) Italy Tel. +39.039.9897.1
Fax +39.039.9897.363 C.F. / P.IVA 06358330964
sales@sy.es.eu | www.syes.eu